## Datasheet and description



# Avide LED Flood Light Rechargeable 20W NW 4000K

**Product code:** ABRFLNW-20W

**Brand link:** avidelighting.com/qr/ABRFLNW-20W

**ID:** AB-190518

**Company name:** Bramcke Hungary Kft.

Company address: Kishatár utca 17., 4031 Debrecen



Date of issue: 2025-04-25

Page: 1/3

#### **SPECIFICATIONS**

EAN code: 5999097907109

Warranty:

Built-in battery: Yes

Working temperature: -20 - +40 °C Packaging:  $1/b \ 10/c \ 160/p$ 

Certifications: CE

#### **TECHNICAL DETAILS**

Wattage: 20W

Voltage: 100-265V Beam angle: 120°

Dimmability: No

Lumen output: 1 100lm
Color temperature: 4 000K
Lifetime: 25 000h

Energy class: G

Type of LED: COB

CRI: >70

IP standard: IP65

#### **BOX PICTURE**



## Datasheet and description



# Avide LED Flood Light Rechargeable 20W NW 4000K

**Product code:** ABRFLNW-20W

**Brand link:** avidelighting.com/qr/ABRFLNW-20W

**ID:** AB-190518

**Company name:** Bramcke Hungary Kft.

Company address: Kishatár utca 17., 4031 Debrecen



Date of issue: 2025-04-25

Page: 2/3

#### **PRODUCT SIZE**

Width: 220mm Height: 300mm Depth: 185mm

#### **CARDBOARD BOX**

EAN: 5999097907109 Packaging: 1/b 10/c 160/p

Dimensions: 220mm x 220mm x 150mm

Net weight: 1 210g Gross weight: 1 250g

### **CARTON**

EAN: 5999097907116 Packaging: 1/b 10/c 160/p

Dimensions: 770mm x 460mm x 240mm

Net weight: 12.1kg
Gross weight: 12.5kg

#### **PALLET EXAMPLE**

Height:

Width: 120cm (std Euro pallet)
Mepth: 80cm (std Euro pallet)


Cartons per pallet: 16carton/pallet

Cartons per row: 2pcs
Net weight: 193.6kg
Gross weight: 200kg

#### **PRODUCT PICTURE**



#### PRODUCT OUTLINE



### Datasheet and description



## Avide LED Flood Light Rechargeable 20W NW 4000K

Product code: ABRFLNW-20W

**Brand link:** avidelighting.com/qr/ABRFLNW-20W

**ID:** AB-190518

**Company name:** Bramcke Hungary Kft.

Company address: Kishatár utca 17., 4031 Debrecen



Date of issue: 2025-04-25

Page: 3/3

#### **PRODUCT DESCRIPTION**

The battery-operated Avide COB LED floodlights enable portable, mobile use. Brightness is adjustable in two stages. They can provide the same brightness as traditional halogen floodlights but with much lower power consumption; thus when operated from a battery, they can ensure a longer operating time. The battery of the floodlight can be fully charged in 3 hours and with one full charge it can operate for up to 5 hours. COB (chip-on-board) represents one of the most recent LED technologies, focusing the emitted light much better and thus providing better lighting at a longer distance. LED floodlights can provide up to 20 times longer lifetime compared to products using traditional light bulbs. Due to its IP65 classification, it is perfectly suitable for both indoor and outdoor use. The edge of the floodlight features a metal frame that makes it possible to be turned and tilted, thus enabling you to adjust the adequate lighting angle.

Do not look directly into the floodlight! Do not use the fixture under water! The lamp can be charged only with the supplied chargers! Using another charger may cause a malfunction or accident! Make sure that the lamp is switched off during charging. Otherwise the battery may malfunction or may become inoperable.

The package includes both an AC and a car charger, thus you may charge your light even on the go.

The Avide battery-operated floodlights are available in neutral white (NW) / cold white (CW) color temperatures in 10 W and 20 W power output versions, and with another design, they are available in a neutral white (NW) color temperature and a 30W and 50W power output.

The floodlight category includes numerous additional products. Learn more about these on the following link.